

COMPRESSOR DEFINITION

Designation	NE K6212Z
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	269AA51

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor				
2 Refrigerant	R-134a				
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]			
4 Application type	High Back Pressure (Commercial Compressors)				
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)			
5 Motor type	CSIR				
6 Starting torque	HST - Hight starting torque				
7 Expantion device	Capillary tube or Expansion valve				
8 Compressor cooling	Operating voltage range				
		50 Hz	60 Hz		
8.1 LBP (32°C Ambient temperature)	-	-	-		
8.2 LBP (43°C Ambient temperature)	-	-	-		
8.3 HBP (32°C Ambient temperature)	-	-	-		
8.4 HBP (43°C Ambient temperature)	-	-	-		
9 Maximum condensing pressures/temperature					
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F		
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F		
10 Maximum winding temperature	130	[°C]			

B - MECHANICAL DATA

1 Commercial designation	1/2	[hp]
2 Displacement	14.28	[cm ³] (0.871 cu.in)
2.1 Bore [mm]	30.157	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.2	[kg] (24.69 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRP-0012	
3 Start capacitor	72-88(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0741/G6	
6 Start winding resistance	30.40	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	4.20	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	19.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - IMQ	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
4484	1130	1314	628	3.78	29.07	7.14	1.80	2.09

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	2222	560	651	351	2.87	12.02	6.34	1.60	1.86
-10	(+14)	2770	698	812	380	2.95	15.03	7.29	1.84	2.14
-5	(+23)	3450	869	1011	415	3.05	18.79	8.31	2.09	2.43
0	(+32)	4263	1074	1249	455	3.18	23.32	9.36	2.36	2.74
+5	(+41)	5209	1313	1526	499	3.32	28.66	10.43	2.63	3.06
+10	(+50)	6287	1584	1842	549	3.51	34.81	11.47	2.89	3.36

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	1990	502	583	374	2.90	11.63	5.31	1.34	1.56
-10	(+14)	2481	625	727	413	3.02	14.55	6.02	1.52	1.76
-5	(+23)	3090	779	905	455	3.16	18.19	6.80	1.71	1.99
0	(+32)	3817	962	1118	500	3.31	22.58	7.64	1.93	2.24
+5	(+41)	4662	1175	1366	548	3.49	27.74	8.51	2.14	2.49
+10	(+50)	5625	1417	1648	600	3.69	33.71	9.36	2.36	2.74

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	1682	424	493	387	2.94	10.72	4.36	1.10	1.28
-10	(+14)	2134	538	625	438	3.10	13.65	4.87	1.23	1.43
-5	(+23)	2690	678	788	491	3.28	17.28	5.47	1.38	1.60
0	(+32)	3349	844	981	546	3.47	21.63	6.14	1.55	1.80
+5	(+41)	4112	1036	1205	602	3.68	26.73	6.84	1.72	2.00
+10	(+50)	4978	1254	1459	660	3.91	32.60	7.55	1.90	2.21

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		